#### **Technical Data Sheet**

# **Pure Citrus Solvent**

#### **Features**

- No Petrochemicals
- Natural Aroma
- 3 x Stronger than Mineral Spirits
- Tree Based



Limitations



Colors

## **General Properties**

Cleaner and solvent for oil based paints. Pure Citrus Solvent is not water imiscible.

# **Locally Harvested Ingredients**

**D-Limonene** 

## **Recommended For**

Cleaning, diluting oil based paints. Cleaning.

#### **Technical Data**

Vehicle Type: D-limonene Pigment Type: None,

Volume Solids: 100% Solvent

Theoretical Coverage at 75 F (23 C) and 50% humidity:

Typically added at a rate of 1:4 or 20% by volume.

Recommended Film Thickness

Dry Time @ 77 F (25 C) @ 50% R.H.

**Dries By: Evaporation** 

Avoid prolonged skin contact. Avoid inhalation. Use with ventilation. Product is a strong, natural solvent that works very well and does very little harm. It must be used carefully. Always test for personal sensitivities and preferences in small inconspicuous areas before application to the entire surface.

1 11

Containers are a leading contributor to landfill mass. Recycle containers whenever possible. Earthpaint reuses and recycles containers. Clean containers can be reused by Earthpaint Inc. Call for more information.

Recycle

### **Cautions**

Health Precautions: Use in adequate ventilation. Avoid breathing vapors or spray mist. Can cause skin, eye and lung sensitivities or irritation. Use NIOSH approved respirator. Wear protective clothing, gloves, and goggles. Flash point above 115 F. Do not ingest. If irritation occurs contact physician.

Contact Nationwide Poison Center Hotline: 1.800.222.1222

Flash Point: Not Less than 112F degrees Fahrenheit

Minimum: 40 F Maximum: 90 F, **Dilution**:

Water up to 95% Clean Up: Water

Weight Per Gallon: 7.9 lbs Storage Temperature:

Minimum: 38 F Maximum: 90 F Shelf Life: 2 yr

(Volatile Organic Compounds (VOC): Less than 848 grams / liter from Pure Citrus

Distillate.

**SPONTANEOUS COMBUSTION WARNING:** Oil damp or soaked rags or paper stored in dry containers or in piles can self ignite. Soak in water in metal containers, rinse well, dry flat in open air and then compost. It is against the law to dispose of liquid paint or paint products into sewers or land fill.

## LIMITED WARRANTY

Earthpaint Inc. warrants that this product meets Earthpaint Inc.'s manufacturing specifications. If this product does not meet these specifications, Earthpaint Inc. will, at its option and upon proof of purchase, either furnish an equivalent amount of new product to you or refund the purchase price of this product. In no event will Earthpaint Inc. be responsible for (1) labor or the cost of labor for removal or application of any product; or (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

Always test for personal sensitivities and preferences in small inconspicuous areas before application to the entire surface.

Made By Earthpaint Inc. Asheville, NC 28806 Customer support: admin@earthpaint.net

Check out our other products at

www.earthpaint.net